

The Commercial
LED Lighting Specialist

Superlight®

LED STRIP LIGHTS

PRODUCT CATEGORY DATA SHEET

PRODUCT DATA SHEET

LED STRIP LIGHT | 220VAC-2835



FEATURES:

Brand	Superlight
Voltage	220 VAC
Power	10 w/m
IP Rating	IP65
LED Chip	SMD 2835
LED Quantity	144 LEDs/m
PCB Width	10 mm
Length	100 m/roll
Cutting point	1 m
Beam Angle	120°
Colour Rendering	CRI >80
Lumens	864 Lm/m
LED Lumens	22-24 Lm/LED
Colour Temp.	3000K/4000K/6500K
Warranty	One year



2835



10



IP65



220VAC



1m


ITEM No.

220VAC-2835-144P-Flat

Strip LED Accessories



Power Supply



Straight Connector



End Cap

PRODUCT DATA SHEET

LED STRIP LIGHT | 220VAC-2835



FEATURES:

Brand	Superlight
Voltage	220 VAC
Power	10 w/m
IP Rating	IP65
LED Chip	SMD 2835
LED Quantity	144 LEDs/m
PCB Width	10 mm
Length	100 m/roll
Cutting point	1 m
Beam Angle	120°
Colour Rendering	CRI >80
Lumens	864 Lm/m
LED Lumens	22-24 Lm/LED
Colour Temp.	3000K/4000K/6500K
Warranty	One year




ITEM No.

220VAC-2835-144P-Flat White-Diffuser

Strip LED Accessories



Power Supply



Straight Connector



End Cap

PRODUCT DATA SHEET

LED STRIP LIGHT | 12VDC-2835



2835



9



IP65



12VDC



25mm

FEATURES:

Brand	Superlight
Voltage	12 VDC
Power	9 w/m
IP Rating	IP65
LED Chip	SMD 2835
LED Quantity	120 LEDs/m
PCB Width	8 mm
Length	5 m
Cutting point	25 mm
Beam Angle	120°
Colour Rendering	CRI >80
PCB	White 25/50 um
Connector	2 Wires
Lumens	790 Lm/m
LED Lumens	24-26 Lm/LED
Colour Temp.	3000K/4000K
Warranty	One year

ITEM No.

12VDC-2835-120P-IP65

CAUTION

- Storage Temperature: -40 ~ +80°C,
Operating Temperature: -25 ~ +60°C.
- Installation surface must be smooth, clean and dry.
- The part of LED components can not be fixed on the surface of the sharp edge.
- Strip should not be collided or crushed.
- Strip can be cut following the cutting lines.
- The LED strips, must not exceed 5 meters, when used in a DC series circuit.

PRODUCT DATA SHEET

LED STRIP LIGHT | 24VDC-2835



2835



9,9



IP65



24VDC



50mm

FEATURES:

Brand	Superlight
Voltage	24 VDC
Power	9,9 w/m
IP Rating	IP65
LED Chip	SMD 2835
LED Quantity	120 LEDs/m
PCB Width	8 mm
Length	5 m
Cutting point	50 mm
Beam Angle	120°
Colour Rendering	CRI >80
PCB	White 25/50 um
Connector	2 Wires
Lumens	900 Lm/m
LED Lumens	24-26 Lm/LED
Colour Temp.	3000K/4000K
Warranty	One year

ITEM No.

24VDC-2835-120P-IP65

CAUTION

- Storage Temperature: -40 ~ +80°C,
Operating Temperature: -25 ~ +60°C.
- Installation surface must be smooth, clean and dry.
- The part of LED components can not be fixed on the surface of the sharp edge.
- Strip should not be collided or crushed.
- Strip can be cut following the cutting lines.
- The LED strips, must not exceed 5 meters, when used in a DC series circuit.

PRODUCT DATA SHEET

LED STRIP LIGHT | 24VDC-2835 Tunable



FEATURES:

Brand	Superlight
Voltage	24 VDC
Power	9,9 w/m
IP Rating	IP65
LED Chip	SMD 2835
LED Quantity	120 LEDs/m
PCB Width	8 mm
Length	5 m
Cutting point	100 mm
Beam Angle	120°
Colour Rendering	CRI >80
PCB	White 25/25 um
Connector	3 Fils
LED Lumens	24-26 Lm/LED
Colour Temp.	3000K to 6500K Tunable
Warranty	One year



2835



9,9



IP65



24VDC



100mm

ITEM No.

24VDC-2835-120P-IP65 Tunable

CAUTION

- Storage Temperature: -40 ~ +80°C,
Operating Temperature: -25 ~ +60°C.
- Installation surface must be smooth, clean and dry.
- The part of LED components can not be fixed on the surface of the sharp edge.
- Strip should not be collided or crushed.
- Strip can be cut following the cutting lines.
- The LED strips, must not exceed 5 meters, when used in a DC series circuit.

PRODUCT DATA SHEET

LED STRIP LIGHT | 24VDC-5050 RGBW

Superlight®



FEATURES:

Brand	Superlight
Voltage	24 VDC
Power	18 w/m
IP Rating	IP65
LED Chip	SMD 5050 4 in 1
LED Quantity	60 LEDs/m
PCB Width	12 mm
Length	5 m
Cutting point	100 mm
Beam Angle	120°
Colour Rendering	CRI >80
PCB	White 25/50 um
Connector	5 Fils
Colour Temp.	3000K to 6500K RGBW
Warranty	One year



5050



18



IP65



24VDC



100mm

ITEM No.

24VDC-5050-60P-IP65 RGBW

CAUTION

- Storage Temperature: -40 ~ +80°C,
Operating Temperature: -25 ~ +60°C.
- Installation surface must be smooth, clean and dry.
- The part of LED components can not be fixed on the surface of the sharp edge.
- Strip should not be collided or crushed.
- Strip can be cut following the cutting lines.
- The LED strips, must not exceed 5 meters, when used in a DC series circuit.

LED STRIP LIGHT

Summary

Model Number	Power	Length	Cutting point	IP Rating	Colour Temperature
220VAC-2835-144P-Flat	10w/m	100m/roll	1m	IP65	3000K/4000K/6500K
220VAC-2835-144P-Flat White-Diffuser	10w/m	100m/roll	1m	IP65	3000K/4000K/6500K
12VDC-2835-120P-IP65	9w/m	5m	25mm	IP65	3000K/4000K
24VDC-2835-120P-IP65	9,9w/m	5m	50mm	IP65	3000K/4000K
24VDC-2835-120P-IP65 Tunable	9,9w/m	5m	100mm	IP65	3000K to 6500K Tunable
24VDC-5050-60P-IP65 RGBW	18w/m	5m	100mm	IP65	3000K to 6500K RGBW