


Led Recessed Panel Light | 50W 1200×290mm CUT-OUT (47"×11")

LED RECESSED PANEL LIGHT

50W 1200×290mm cut-out (47"×11")




Dimensions:



Light & Lux Distribution Curve:

MP: MicroPrismatic 90°



<https://www.superlight.tn>

Key Data:

Power	50W
IP Rating	IP40
Dimensions	1195×295×32mm
Cut-out size	1200×290mm
Luminous Flux	5500Lm
Colour Temperature	4000K/6500K
Warranty	three years

Model No.

PL REC 50W

Technical Specifications:

Input Voltage	220-240V AC
Power Factor	0.9
LED Type	SMD 2835
LED Luminous Flux	6759Lm
Luminous Efficacy	110Lm/W
UGR	UGR<19
LED Manufacturer	San'an
SDCM	< 3
Service Life	L80 / B10 > 50,000 h
LED Circuit Mode	(4)S*(18)P=(72)PCS
LED Board Base Type	Aluminium
Driver Output	25-42VDC 1200mA
Driver Specifications	Isolated
Total Circuit Power (W)	50±0.5
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	90°
Supply Current	220mA
Working Temp.	-20°C ~ +45°C
Lifespan	50,000 hours
Risk Group achieved	RG0
Fire Rating	V-0
Energy Efficiency Index (EEI)	0.14 (A+)
Impact Resistance	IK04 (IK10 optional)
Flick Free	Yes
Housing Color	RAL9016 White
Housing Material	Aluminum/white
Lens Material	Acrylic (PMMA)
Diffuser Material	Polystyrene (PS)
Weight	5000g

Product Features:

1. Using high lumen SMD light source.
2. Using good reflectivity light, it is thinner and brighter.
3. Low voltage & constant current driver and no glare.
4. This product can show high brightness.

Led Recessed Panel Light | 50W 1200×290mm CUT-OUT (47"×11")

Superlight[®]