LED FLOOD LIGHT 200W

400*260mm



KEY DATA

Power	200W
IP Rating	IP65
Dimension	400*260mm
Luminous Flux	20000 Lm
Colour Temperature	3000K°/4000K°/6500K°
Warranty	Two years
-	

Model Number SFL 200w-PC

TECHNICAL SPECIFICATIONS

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM
-/+180 -150 -120 -90 -60 -60 -60 -60 -60 -60 -60 -60 -60 -6

AVERAG	E BEAN	1 ANĞI	E (50	0%):11	15.1 DE
CO PLA	NE ISOL	UX DIA	GRAM	(UNIT:	lx)
3					
4		A			
5	-\/-	$\perp \downarrow \downarrow$			
6		$\mathcal{A}\mathcal{A}$			
7	\longrightarrow	/ //			
8	+	/ /	/		
9	+4				
10					
11					
0.0		4.5			9.0
	840 700	_		140 110	S (m)
	560 420			70.0 56.0	

_	
https:/	/www.superlight.tn

Input Voltage	AC 170-265V
Power Factor	0,97
LED Type	SMD 2835
LED Luminous Flux	20000 Lm
Luminous Efficacy	100Lm/W
LED Manufacturer	CINDA
Frequency/Current	50HZ/0,91A
led board Base Type	AL 1060
Dimmable	NO
Total Circuit Power (W)	200W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	110°
Certificate	Pass LVD
Lens Material	Polycarbonate
Lifespan	25,000 hours
Material of heat sink	ADC12
Mounting Bracket	SPCC
Input cable length	200mm(H05RN-F 3*1,0mm2)
Weight	2035g

PRODUCT FEATURES:

- 1.Using high lumen SMD light source
- 2.Using good reflectivity light, it is thinner and brighter, the light is more equally.
- 3.Low voltage & constant current driver, no glare, the light is soft.
- 4.Launch in 0.01sec, no flashing, no noise, no radiation and energy saving.
- 5. This product can show high brightness, without seeing the lamp itself.